

ginkoLam



**QUALITY DIGITAL
SOLUTIONS**

#12, 5815 - 40 Street S.E.
Calgary, Alberta, T2C 2H6



403.262.6915 888.235.2838
qualitydigitalsolutions.ca

HEAT ASSIST LAMINATOR WIDTH 1,65M - 65"

Ideal working tool for finishing your eco solvent, latex, offset and screen printing.

This entry-level laminator is the perfect machine for one-off or medium-sized jobs and completes the most common lamination requirements in the field of signage, photography and printing:
Lamination, Pre-mask, Mounting up to 45 mm.

With the acquisition of a GinkoLam laminator, you are guaranteed impeccable lamination results and rapid mastering of your finishing by all of your teams.



Pressure is applied with a compressor, included with the machine

This laminator is delivered assembled on its stand for a quick installation and set up in your premises.

The CE certification of this machine has been carried out by the APAVE laboratory in France in full compliance with the latest European machine directives.



ginkoLam



PRESSURE



The movement of the upper roller is controlled by a compressor, supplied with the machine. It is very simple to operate with an easily accessible lever for an opening up to 45mm.



LINEAR COUNTER

To check the status of your work, very useful when working roll to roll or to indicate the remaining material on your media reels



LAMINATED PRINT REWINDER

Integrated at the back of the machine. A single technician operation, without a risk of damaging your prints once laminated.



CONTROL BOARD

This easy to use control board manages all the operation of the laminator.

MEDIA SET-UP

Lamination film

Take up of the lamination film protection liner



Roll of print or waste paper

Laminated print rewinder

4 shafts are delivered with the machine. Brake tension can be applied on each of them.

SAFETIES

Laser sensors in front of the rollers and 2 emergency switches. When activated, the machine needs to be reset simply by pressing on a reset button located in front, after having corrected the default.

TECHNICAL DATA

Maximum thickness media + board	45mm
Maximum working width	160cm
Maximum film width	20cm
Usable length of lamination media	165cm
Diameter of the roller	130mm
Temperature of the heating roller	up to 60°C
Heating time from room temperature to 40 °C (86 °F)	10 minutes
Shafts delivered with the machine	4 shafts
Adjustable speed	From 1 to 5 m/mn
Power W – Voltage – Amps	230V- 50/60Hz - 2.5 kW
Dimensions of the machine L x D x H cm	202 x 58 x 126
Net weight of the machine	147kg
Shipping dimensions L x D x H cm	215 x 75 x 150
Shipping weight	227kg
Warranty	1 an
Made in China , CE certification delivered by a French testing laboratory under the latest European directives.	



QUALITY DIGITAL SOLUTIONS

#12, 5815 - 40 Street S.E.
Calgary, Alberta, T2C 2H6



403.262.6915 888.235.2838
qualitydigitalsolutions.ca